


General Description

KEC Field Stop Trench IGBTs offer low switching losses, high energy efficiency and short circuit ruggedness.

It is designed for applications such as motor control, uninterrupted power supplies(UPS), general inverters.

FEATURES

- High speed switching
- High system efficiency
- Short Circuit Withstand Times 10us
- Extremely enhanced avalanche capability




MAXIMUM RATING (Ta=25 °C)

CHARACTERISTIC	SYMBOL	RATING	UNIT	
Collector-Emitter Voltage	V_{CES}	1200	V	
Gate-Emitter Voltage	V_{GES}	± 20	V	
Collector Current	I_C	@Tc=25	80	A
		@Tc=100	40	A
Pulsed Collector Current	I_{CM}^*	120	A	
Diode Continuous Forward Current	@Tc=100	I_F	40	A
Diode Maximum Forward Current		I_{FM}	160	A
Maximum Power Dissipation	P_D	@Tc=25	357	W
		@Tc=100	140	W
Maximum Junction Temperature	T_j	150		
Storage Temperature Range	T_{stg}	-55 to + 150		

*Repetitive rating : Pulse width limited by max. junction temperature

THERMAL CHARACTERISTIC

CHARACTERISTIC	SYMBOL	MAX.	UNIT
Thermal Resistance, Junction to Case (IGBT)	R_{thJC}	0.35	/W
Thermal Resistance, Junction to Case (DIODE)	R_{thJC}	1.1	/W
Thermal Resistance, Junction to Ambient	R_{thJA}	40	/W




KGF40N120KDA

ELECTRICAL CHARACTERISTICS (Ta=25)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT	
Static							
Collector-Emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=1mA$	1200	-	-	V	
Collector Cut-off Current	I_{CES}	$V_{GE}=0V, V_{CE}=1200V$	-	-	1.0	mA	
Gate Leakage Current	I_{GES}	$V_{CE}=0V, V_{GE}=\pm 20V$	-	-	± 100	nA	
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=40mA$	4.5	6.0	7.5	V	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=40A$	-	1.9	2.25	V	
		$V_{GE}=15V, I_C=40A, T_C = 125$	-	2.2	-	V	
		$V_{GE}=15V, I_C=80A$	-	2.5	-	V	
Dynamic							
Total Gate Charge	Q_g	$V_{CC}=600V, V_{GE}=15V, I_C= 40A$	-	230	350	nC	
Gate-Emitter Charge	Q_{ge}		-	30	-	nC	
Gate-Collector Charge	Q_{gc}		-	110	-	nC	
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=600V, I_C=40A, V_{GE}=15V, R_G=10$ Inductive Load, $T_C = 25$	-	60	-	ns	
Rise Time	t_r		-	45	-	ns	
Turn-Off Delay Time	$t_{d(off)}$		-	310	-	ns	
Fall Time	t_f		-	70	-	ns	
Turn-On Switching Loss	E_{on}		-	3.5	5.2	mJ	
Turn-Off Switching Loss	E_{off}		-	1.9	2.8	mJ	
Total Switching Loss	E_{ts}		-	5.4	8.0	mJ	
Turn-On Delay Time	$t_{d(on)}$		$V_{CC}=600V, I_C=40A, V_{GE}=15V, R_G=10$ Inductive Load, $T_C = 125$	-	60	-	ns
Rise Time	t_r			-	50	-	ns
Turn-Off Delay Time	$t_{d(off)}$			-	350	-	ns
Fall Time	t_f	-		175	-	ns	
Turn-On Switching Loss	E_{on}	-		4.3	6.4	mJ	
Turn-Off Switching Loss	E_{off}	-		3.0	4.5	mJ	
Total Switching Loss	E_{ts}	-		7.3	10.9	mJ	
Input Capacitance	C_{ies}	$V_{CE}=30V, V_{GE}=0V, f=1MHz$	-	4800	-	pF	
Output Capacitance	C_{oes}		-	195	-	pF	
Reverse Transfer Capacitance	C_{res}		-	135	-	pF	
Short Circuit Withstand Time	t_{sc}		$V_{CC}=600V, V_{GE}=15V, T_C=100$	10	-	-	μs

Marking



KGF40N120KDA

ELECTRICAL CHARACTERISTIC OF DIODE

CHARACTERISTIC	SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Diode Forward Voltage	V_F	$I_F = 40A$	$T_C = 25$	-	2.2	2.6	V
			$T_C = 125$	-	1.9	-	
Diode Reverse Recovery Time	t_{rr}	$I_F = 40A$	$T_C = 25$	-	360	520	ns
			$T_C = 125$	-	460	-	
Diode Peak Reverse Recovery Current	I_{rr}	$I_F = 40A$ $di/dt = 200A/\mu s$	$T_C = 25$	-	16	21	A
			$T_C = 125$	-	19	-	
Diode Reverse Recovery Charge	Q_{rr}	$I_F = 40A$ $di/dt = 200A/\mu s$	$T_C = 25$	-	2800	4200	nC
			$T_C = 125$	-	5200	-	

KGF40N120KDA

Fig 1. Saturation Voltage Characteristics




Fig 2. Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature




Fig 4. Saturation Voltage vs. V_{GE}




Fig 5. Saturation Voltage vs. V_{GE}





Fig 6. Capacitance Characteristics



KGF40N120KDA

Fig 7. Turn-On Characteristics vs. Gate Resistance




Fig 8. Turn-Off Characteristics vs. Gate Resistance




Fig 9. Switching Loss vs. Gate Resistance




Fig 10. Turn-On Characteristics vs Collector Current




Fig 11. Turn-Off Characteristics vs Collector Current





Fig 12. Switching Loss vs. Collector Current



KGF40N120KDA

Fig 13. Gate Charge Characteristics




Fig 14. SOA Characteristics




Fig 15. Turn-Off SOA





Fig 16. Transient Thermal Impedance of IGBT



KGF40N120KDA

Fig 17. Forward Characteristics




Fig 18. Reverse Recovery Current





Fig 19. Reverse Recovery Time



KGF40N120KDA

Fig 21. Switching Test Circuit




Fig 22. Definition Switching Time & Loss




Fig 23. Definition Diode Switching Time

