



E3Z-T86

Photoelectric sensor, rectangular housing, infrared LED, through-beam, 15 m, PNP, Light-ON/Dark-ON, M8 4-pin connector

Specifications

Shape	Cuboid
Sensing method	Through-beam
Sensing distance	15000 mm
Setting method	Manual adjustment
Connection method	Connector M8 - 4 pin
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	PBT
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	31 mm
Product Depth (unpacked)	20 mm
Type of light	Infrared light
Power supply voltage	12-24 V
Degree of protection (IP)	IP67



E39-L203

Mounting bracket for E3AS sensor, rear mounting



E39-L211

Mounting bracket for E3AS sensor, L shaped



E39-L212

Protective mounting bracket for E3AS, vertical mounting



E39-L214

Protective metal cover for E3AS, horizontal surface mounting



E39-S65A

Slit for E3Z-T, 0.5mm diameter



E39-S65B

Slit for E3Z-T, 1mm diameter



E39-S65C

Slit for E3Z-T, 2mm diameter

E39-S65D

Slit for E3Z-T, 0.5 x 10 mm dia.

E39-S65E

Slit for E3Z-T, 1x10mm diameter



E39-S65F

Slit for E3Z-T, 2x10mm diameter

Related products



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

CAD Library



E3Z Brochure

EN PDF 1.34 MB



E3Z Compact Photoelectric Sensor with Built-in Amplifier Datasheet

EN PDF 3.13 MB



E3Z IO-Link Index list

EN PDF 1.89 MB



IO-Link Series Brochure

EN PDF 6.26 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 10.2 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 12 October, 2023. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)